

Description

Fastener Length: 5/8", Thread Size: 5/32"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | BACB30JC5A4SU |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5320-01-355-1484 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |
| National Motor Freight: | 096320, Rivets I / S Nickel Plated Buffed |

NO IMAGE
AVAILABLE

P/N BACB30JC5A4SU Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Fastener Length: | 0.6145 Inches Minimum And 0.6345 Inches Maximum |
| Head Style: | Flush Countersunk |
| Width Between Flats: | 0.0791 Inches Minimum And 0.0801 Inches Maximum |
| Shank Diameter: | 0.2888 Inches Minimum And 0.3322 Inches Maximum |
| Shank Style: | Pin-rivet, Straight, Threaded |
| Head Major Diameter: | 0.1630 Inches Minimum And 0.1635 Inches Maximum |
| Lubrication: | Dry Film |
| Grip Length: | 0.3065 Inches Minimum And 0.3175 Inches Maximum |
| Thread Quantity Per Inch: | 32 |
| Nominal Thread Size: | 0.1640 Inches |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams 5731 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjc |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30JC5A4SU> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.