

Description

Fastener Length: 1-17/64", Thread: 1/4-28, Head Width: 3/32", Thread Length: 13/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | BACB30JC814 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-00-933-7291 |
| Schedule B: | 7318.24.0000 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N BACB30JC8-14 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.380 Inches Minimum And 0.410 Inches Maximum |
| Fastener Length: | 1.260 Inches Minimum And 1.280 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.464 Inches Minimum And 0.510 Inches Maximum |
| Grip Diameter: | 0.2485 Inches Minimum And 0.2495 Inches Maximum |
| Internal Drive Style: | Hexagon |
| Nominal Thread Diameter: | 0.250 Inches |
| Grip Length: | 0.870 Inches Minimum And 0.880 Inches Maximum |
| Width Across Flats: | 0.095 Inches Minimum And 0.097 Inches Maximum |
| Thread Quantity Per Inch: | 28 |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Surface Finish: | 32.0 Microinches Grip |
| Surface Finish: | 63.0 Microinches Bearing Surface Of Head |
| Special Features: | Drilled Hole Thd End 0.122 To 0.142 In. Dia,0.200 In. Deep |
| Material: | Steel Comp 4130 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/BACB30JC8-14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.