

Description

Fastener Length: 1-47/64", Thread Size: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	BACB30KD6A21X
Minimum Qty (MOQ):	1 EA
NSN:	5320-01-504-9622
Schedule B:	7318.15.2010
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N BACB30KD6A21X Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	1.709 Inches Minimum And 1.734 Inches Maximum
Head Style:	Flush Countersunk
Shank Diameter:	0.397 Inches Minimum And 0.421 Inches Maximum
Shank Style:	Pin-rivet, Tapered, Threaded
Head Major Diameter:	0.561 Inches Minimum And 0.613 Inches Maximum
Tip Diameter:	0.368 Inches Minimum And 0.373 Inches Maximum
Lubrication:	Cetyl Alcohol
Grip Length:	1.303 Inches Minimum And 1.318 Inches Maximum
Thread Quantity Per Inch:	24
Nominal Thread Size:	0.375 Inches
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416, Type II, Class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30KD6A21X> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.