

P/N BACB30KZ4-33

Description

Fastener Length: 1-1/32", Thread: 1/4-28, Thread Length: 0-63/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: BACB30KZ433

Minimum Qty (MOQ):

NSN: 5306-01-058-8387

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)







^{*} See page 2 for technical characteristics

P/N BACB30KZ4-33 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.956 Inches Minimum And 1.016 Inches Maximum
Fastener Length:	1.016 Inches Minimum And 1.046 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.125 Inches Minimum And 0.140 Inches Maximum
Width Between Flats:	0.430 Inches Minimum And 0.439 Inches Maximum
Nominal Thread Diameter:	0.250 Inches
Features Provided:	Finished Head
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Material:	Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unf
Specification/standard Data:	81205-bacb30kz Manufacturers Standard

How to Order

Order this machine bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/BACB30KZ4-33 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.