

Description

Fastener Length: 41/64", Hole Diameter: 1/32", Thread: 10-32, Thread Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACB30LE3HU4
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-231-9338
Schedule B:	7318.15.8085
ECCN:	9A991



* See page 2 for technical characteristics

P/N BACB30LE3HU4 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.390 Inches Nominal
Fastener Length:	0.625 Inches Minimum And 0.655 Inches Maximum
Head Style:	Double Hexagon W/hole
Head Height:	0.190 Inches Minimum And 0.210 Inches Maximum
Width Between Flats:	0.243 Inches Minimum And 0.251 Inches Maximum
Extended Washer Diameter:	0.359 Inches Minimum And 0.369 Inches Maximum
Extended Washer Thickness:	0.040 Inches Minimum And 0.060 Inches Maximum
Hole Diameter:	0.032 Inches Minimum And 0.042 Inches Maximum
Grip Diameter:	0.1890 Inches Minimum And 0.1895 Inches Maximum
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.240 Inches Minimum And 0.260 Inches Maximum
Hole Quantity:	4
Hole Type:	Drilled
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	200000 Pounds Per Square Inch
Hole Configuration Style:	Double Hexagon Longitudinal Hole
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30LE3HU4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.