



Military-Fasteners.com

P/N BACB30LE5-22

Description

Fastener Length: 1-31/32", Thread: 1/4-24, Thread Length: 39/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACB30LE522
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-048-9660
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N BACB30LE5-22 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.568 Inches Minimum And 0.618 Inches Maximum
Fastener Length:	1.953 Inches Minimum And 1.983 Inches Maximum
Head Style:	Double Hexagon W/hole
Head Height:	0.309 Inches Minimum And 0.329 Inches Maximum
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Extended Washer Diameter:	0.575 Inches Minimum And 0.585 Inches Maximum
Extended Washer Thickness:	0.040 Inches Minimum And 0.060 Inches Maximum
Grip Diameter:	0.3110 Inches Minimum And 0.3120 Inches Maximum
Nominal Thread Diameter:	0.312 Inches
Grip Length:	1.365 Inches Minimum And 1.385 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	200000 Pounds Per Square Inch
Material:	Iron Alloy 660 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	81205-bacs12le Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30LE5-22> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.