

**Description**

Fastener Length: 1-11/32", Hole Diameter: ", Thread: 1/4-24, Thread Length: 39/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	BACB30LE5HU12
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-040-4698
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N BACB30LE5HU12 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.568 Inches Minimum And 0.618 Inches Maximum
<b>Fastener Length:</b>	1.328 Inches Minimum And 1.358 Inches Maximum
<b>Head Style:</b>	Double Hexagon W/hole
<b>Head Height:</b>	0.309 Inches Minimum And 0.329 Inches Maximum
<b>Width Between Flats:</b>	0.367 Inches Minimum And 0.376 Inches Maximum
<b>Extended Washer Diameter:</b>	0.575 Inches Minimum And 0.585 Inches Maximum
<b>Extended Washer Thickness:</b>	0.040 Inches Minimum And 0.060 Inches Maximum
<b>Hole Diameter:</b>	0.055 Inches Nominal
<b>Grip Diameter:</b>	0.3115 Inches Minimum And 0.3120 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.312 Inches
<b>Grip Length:</b>	0.740 Inches Minimum And 0.760 Inches Maximum
<b>Hole Quantity:</b>	4
<b>Hole Type:</b>	Drilled
<b>Thread Quantity Per Inch:</b>	24
<b>Minimum Tensile Strength:</b>	200000 Pounds Per Square Inch
<b>Hole Configuration Style:</b>	Square Longitudinal Hole
<b>Material:</b>	Iron Alloy 660 Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Thread Series Designator:</b>	Unjf
<b>Specification/standard Data:</b>	81205-bacs12le Professional/industrial Association Standard

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30LE5HU12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.