



Military-Fasteners.com

P/N BACB30LE5HU6

Description

Fastener Length: 31/32", Hole Diameter: ", Thread: 1/4-24, Thread Length: 39/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACB30LE5HU6
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-040-3361
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N BACB30LE5HU6 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.568 Inches Minimum And 0.618 Inches Maximum
Fastener Length:	0.953 Inches Minimum And 0.983 Inches Maximum
Head Style:	Double Hexagon W/hole
Head Height:	0.309 Inches Minimum And 0.329 Inches Maximum
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Extended Washer Diameter:	0.575 Inches Minimum And 0.585 Inches Maximum
Extended Washer Thickness:	0.040 Inches Minimum And 0.060 Inches Maximum
Hole Diameter:	0.055 Inches Nominal
Grip Diameter:	0.3115 Inches Minimum And 0.3120 Inches Maximum
Nominal Thread Diameter:	0.312 Inches
Grip Length:	0.365 Inches Minimum And 0.385 Inches Maximum
Hole Quantity:	4
Hole Type:	Drilled
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	200000 Pounds Per Square Inch
Hole Configuration Style:	Square Longitudinal Hole
Material:	Iron Alloy 660 Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unjf
Specification/standard Data:	81205-bacs12le Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30LE5HU6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.