

# P/N BACB30LH3U22

Military-Fasteners.com

#### Description

Fastener Length: 1-47/64", Thread: 10-32, Thread Length: 23/64"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

#### Order this part online

#### **Additional Information**

SKU / Model:	BACB30LH3U22
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-049-4054
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N BACB30LH3U22 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.320 Inches Minimum And 0.370 Inches Maximum
Fastener Length:	1.705 Inches Minimum And 1.735 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.337 Inches Minimum And 0.383 Inches Maximum
Grip Diameter:	0.1890 Inches Minimum And 0.1895 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Grip Length:	1.365 Inches Minimum And 1.385 Inches Maximum
Thread Quantity Per Inch:	32
Countersink Angle:	100.0 Degrees Nominal
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Iron Alloy 660 Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unjf
Specification/standard Data:	81205-bacs12lh Professional/industrial Association Standard

### How to Order

Order this bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/machine+bolts/BACB30LH3U22</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.