



Military-Fasteners.com

P/N BACB30LH3U4

## Description

Fastener Length: 39/64", Thread: 10-32, Thread Length: 3/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	BACB30LH3U4
Minimum Qty (MOQ):	15 EA
NSN:	5305-01-058-0753
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

# P/N BACB30LH3U4 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.310 Inches Minimum And 0.380 Inches Maximum
Fastener Length:	0.570 Inches Minimum And 0.620 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.337 Inches Minimum And 0.383 Inches Maximum
Grip Diameter:	0.1890 Inches Minimum And 0.1895 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
End Item Identification:	Joint Stars Target Radar System;aircraft, Stratolifter C-135;aircraft, Awacs, E-3a
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.240 Inches Minimum And 0.260 Inches Maximum
Thread Quantity Per Inch:	32
Countersink Angle:	100.0 Degrees Nominal
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Iron Alloy 660 Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unjf
Specification/standard Data:	81205-bacb30lh Manufacturers Standard

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30LH3U4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.