

Description

Fastener Length: 1-7/8", Thread: 1/4-28, Thread Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | BACB30LJ4K24 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5306-01-517-4103 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |

NO IMAGE
AVAILABLE

P/N BACB30LJ4K24 Specifications

| | |
|----------------------------------|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.389 Inches Nominal |
| Fastener Length: | 1.889 Inches Nominal |
| Head Style: | Dished Hexagon |
| Head Height: | 0.125 Inches Minimum And 0.140 Inches Maximum |
| Width Between Flats: | 0.430 Inches Minimum And 0.439 Inches Maximum |
| Grip Diameter: | 0.2481 Inches Minimum |
| Nominal Thread Diameter: | 0.250 Inches |
| Grip Length: | 1.500 Inches Nominal |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 90000 Pounds Per Square Inch |
| Material: | Iron Alloy 660 Overall |
| Surface Treatment: | Aluminum Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30LJ4K24> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.