

P/N BACB30LJ4U22

Description

Fastener Length: 1-53/64", Thread: 1/4-28, Thread Length: 3/8"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

 SKU / Model:
 BACB30LJ4U22

 Minimum Qty (MOQ):
 5 EA

 NSN:
 5306-01-517-4100

 Schedule B:
 7318.15.8085

ECCN: EAR99



^{*} See page 2 for technical characteristics

P/N BACB30LJ4U22 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.389 Inches Nominal
Fastener Length:	1.829 Inches Nominal
Head Style:	Dished Hexagon
Head Height:	0.125 Inches Minimum And 0.140 Inches Maximum
Width Between Flats:	0.430 Inches Minimum And 0.439 Inches Maximum
Grip Diameter:	0.2490 Inches Minimum
Nominal Thread Diameter:	0.250 Inches
Grip Length:	1.375 Inches Nominal
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	90000 Pounds Per Square Inch
Material:	Iron Alloy 660 Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/BACB30LJ4U22 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/BACB30LJ4U22 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/BACB30LJ4U22 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/BACB30LJ4U22 and selecting the quantity you want then click "add to cart".