

**Description**

Fastener Length: 41/64", Thread: 1/4-28, Thread Length: 13/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | BACB30LJ4U4                               |
| Minimum Qty (MOQ):      | 5 EA                                      |
| NSN:                    | 5306-01-164-8517                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N BACB30LJ4U4 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3a   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Thread Length:</b>                                 | 0.364 Inches Minimum And 0.414 Inches Maximum      |
| <b>Fastener Length:</b>                               | 0.624 Inches Minimum And 0.654 Inches Maximum      |
| <b>Head Style:</b>                                    | Undercut Hexagon                                   |
| <b>Head Height:</b>                                   | 0.125 Inches Minimum And 0.140 Inches Maximum      |
| <b>Width Between Flats:</b>                           | 0.430 Inches Minimum And 0.439 Inches Maximum      |
| <b>Grip Diameter:</b>                                 | 0.2490 Inches Minimum And 0.2496 Inches Maximum    |
| <b>Nominal Thread Diameter:</b>                       | 0.250 Inches                                       |
| <b>Grip Length:</b>                                   | 0.240 Inches Minimum And 0.260 Inches Maximum      |
| <b>Thread Quantity Per Inch:</b>                      | 28   |
| <b>Surface Finish:</b>                                | 32.0 Microinches Bearing Surface Of Head           |
| <b>Surface Finish:</b>                                | 32.0 Microinches Grip                              |
| <b>Surface Finish:</b>                                | 32.0 Microinches Threads                           |
| <b>Material:</b>                                      | Iron Alloy 660 Overall                             |
| <b>Material Document And Classification:</b>          | Ams 5737 Assn Std Single Material Response Overall |
| <b>Surface Treatment:</b>                             | Passivate Overall                                  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec Single Treatment Response Overall |
| <b>Thread Series Designator:</b>                      | Unjf   |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30LJ4U4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.