

P/N BACB30LJ4U7

Military-Fasteners.com

Description

Fastener Length: 53/64", Thread: 1/4-28, Thread Length: 13/32"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	BACB30LJ4U7
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-040-4708
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N BACB30LJ4U7 Specifications

Thread Class:	За
Thread Direction:	Right-hand
Thread Length:	0.364 Inches Minimum And 0.414 Inches Maximum
Fastener Length:	0.811 Inches Minimum And 0.841 Inches Maximum
Head Style:	Undercut Hexagon
Head Height:	0.125 Inches Minimum And 0.140 Inches Maximum
Width Between Flats:	0.430 Inches Minimum And 0.439 Inches Maximum
Grip Diameter:	0.2490 Inches Minimum And 0.2495 Inches Maximum
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.427 Inches Minimum And 0.447 Inches Maximum
Thread Quantity Per Inch:	28
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Iron Alloy 660 Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unjf
Specification/standard Data:	97928-bacb30lj Manufacturers Standard

How to Order

Order this bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/machine+bolts/BACB30LJ4U7</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.