

Description

Fastener Length: 61/64", Thread: 1/4-28, Thread Length: 13/32"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	BACB30LJ4U9
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-200-0661
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N BACB30LJ4U9 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.364 Inches Minimum And 0.414 Inches Maximum
Fastener Length:	0.936 Inches Minimum And 0.966 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.125 Inches Minimum And 0.140 Inches Maximum
Width Between Flats:	0.430 Inches Minimum And 0.439 Inches Maximum
Grip Diameter:	0.249 Inches Minimum And 0.250 Inches Maximum
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.552 Inches Minimum And 0.572 Inches Maximum
Thread Quantity Per Inch:	28
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30LJ4U9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.