

**Description**

Fastener Length: 2-5/64", Thread: 1/4-24, Thread Length: 29/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	BACB30LJ523
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-581-6195
Schedule B:	7318.15.8085
ECCN:	9A991

NO IMAGE  
AVAILABLE

## P/N BACB30LJ5-23 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.449 Inches Minimum And 0.459 Inches Maximum
<b>Fastener Length:</b>	2.033 Inches Minimum And 2.078 Inches Maximum
<b>Head Style:</b>	Dished Hexagon
<b>Head Height:</b>	0.156 Inches Minimum And 0.171 Inches Maximum
<b>Width Between Flats:</b>	0.492 Inches Minimum And 0.502 Inches Maximum
<b>Grip Diameter:</b>	0.3104 Inches Minimum And 0.3120 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.312 Inches
<b>Grip Length:</b>	1.428 Inches Minimum And 1.448 Inches Maximum
<b>Thread Quantity Per Inch:</b>	24
<b>Minimum Tensile Strength:</b>	95000 Pounds Per Square Inch
<b>Surface Finish:</b>	32.0 Microinches Bearing Surface Of Head
<b>Surface Finish:</b>	32.0 Microinches Grip
<b>Surface Finish:</b>	32.0 Microinches Threads
<b>Part Name Assigned By Controlling Agency:</b>	Bolt, Hex Head, 95 Ksi Shear, Short Thread, A286, Nonlocking
<b>Material:</b>	Steel Corrosion Resisting Overall
<b>Material Document And Classification:</b>	Ams 5737 Assn Std Single Material Response Overall Or Ams 5853 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Amsqq-p-416, Ty 2, Cl 2 Plus Bps-f-69 Assn Std Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30LJ5-23> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.