

Description

Fastener Length: 1-35/64", Thread: 3/8-24, Thread Length: 31/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | BACB30LJ6DU17 |
| Minimum Qty (MOQ): | 1 |
| NSN: | 5306-01-040-3362 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N BACB30LJ6DU17 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.445 Inches Minimum And 0.495 Inches Maximum |
| Fastener Length: | 1.517 Inches Minimum And 1.547 Inches Maximum |
| Head Style: | Undercut Hexagon |
| Head Height: | 0.188 Inches Minimum And 0.203 Inches Maximum |
| Width Between Flats: | 0.553 Inches Minimum And 0.564 Inches Maximum |
| Grip Diameter: | 0.3740 Inches Minimum And 0.3745 Inches Maximum |
| Shank Unthreaded Hole Diameter: | 0.106 Inches Minimum First Hole And 0.116 Inches Maximum First Hole |
| Nominal Thread Diameter: | 0.375 Inches |
| Grip Length: | 1.052 Inches Minimum And 1.072 Inches Maximum |
| Thread Quantity Per Inch: | 24 |
| Distance From Head Largest Bearing Surface To Shank Hole Center: | 1.346 Inches Minimum First Hole And 1.396 Inches Maximum First Hole |
| Surface Finish: | 32.0 Microinches Bearing Surface Of Head |
| Surface Finish: | 32.0 Microinches Grip |
| Surface Finish: | 32.0 Microinches Threads |
| Material: | Iron Alloy 660 Overall |
| Surface Treatment: | Passivate Overall |
| Thread Series Designator: | Unf |
| Specification/standard Data: | 81205-bacb30lj Manufacturers Standard |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30LJ6DU17> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.