



Military-Fasteners.com

P/N BACB30LJ6DU17

Description

Fastener Length: 1-35/64", Thread: 3/8-24, Thread Length: 31/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACB30LJ6DU17
Minimum Qty (MOQ):	1
NSN:	5306-01-040-3362
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N BACB30LJ6DU17 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.445 Inches Minimum And 0.495 Inches Maximum
Fastener Length:	1.517 Inches Minimum And 1.547 Inches Maximum
Head Style:	Undercut Hexagon
Head Height:	0.188 Inches Minimum And 0.203 Inches Maximum
Width Between Flats:	0.553 Inches Minimum And 0.564 Inches Maximum
Grip Diameter:	0.3740 Inches Minimum And 0.3745 Inches Maximum
Shank Unthreaded Hole Diameter:	0.106 Inches Minimum First Hole And 0.116 Inches Maximum First Hole
Nominal Thread Diameter:	0.375 Inches
Grip Length:	1.052 Inches Minimum And 1.072 Inches Maximum
Thread Quantity Per Inch:	24
Distance From Head Largest Bearing Surface To Shank Hole Center:	1.346 Inches Minimum First Hole And 1.396 Inches Maximum First Hole
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Iron Alloy 660 Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unf
Specification/standard Data:	81205-bacb30lj Manufacturers Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30LJ6DU17> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.