



Military-Fasteners.com

P/N BACB30LJ6DU19

Description

Fastener Length: 1-43/64", Thread: 3/8-24, Thread Length: 31/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACB30LJ6DU19
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-040-3365
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N BACB30LJ6DU19 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.445 Inches Minimum And 0.495 Inches Maximum
<b>Fastener Length:</b>	1.643 Inches Minimum And 1.673 Inches Maximum
<b>Head Style:</b>	Undercut Hexagon
<b>Head Height:</b>	0.188 Inches Minimum And 0.203 Inches Maximum
<b>Width Between Flats:</b>	0.553 Inches Minimum And 0.564 Inches Maximum
<b>Grip Diameter:</b>	0.3740 Inches Minimum And 0.3745 Inches Maximum
<b>Shank Unthreaded Hole Diameter:</b>	0.106 Inches Minimum First Hole And 0.116 Inches Maximum First Hole
<b>Nominal Thread Diameter:</b>	0.375 Inches
<b>Grip Length:</b>	1.178 Inches Minimum And 1.198 Inches Maximum
<b>Thread Quantity Per Inch:</b>	24
<b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b>	1.472 Inches Minimum All Holes And 1.522 Inches Maximum All Holes
<b>Surface Finish:</b>	32.0 Microinches Bearing Surface Of Head
<b>Surface Finish:</b>	32.0 Microinches Grip
<b>Surface Finish:</b>	32.0 Microinches Threads
<b>Material:</b>	Iron Alloy 660 Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Thread Series Designator:</b>	Unf
<b>Specification/standard Data:</b>	81205-bacb30lj Manufacturers Standard

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30LJ6DU19> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.