

**Description**

Fastener Length: 2-9/16", Thread: 3/8-24, Thread Length: 15/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                    |                  |
|--------------------|------------------|
| SKU / Model:       | BACB30LJ6DU30    |
| Minimum Qty (MOQ): | 1 EA             |
| NSN:               | 5306-01-581-6512 |
| Schedule B:        | 7318.15.8085     |
| ECCN:              | EAR99            |



\* See page 2 for technical characteristics

## P/N BACB30LJ6DU30 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3a   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Thread Length:</b>                                 | 0.465 Inches Minimum And 0.475 Inches Maximum  |
| <b>Fastener Length:</b>                               | 2.518 Inches Minimum And 2.563 Inches Maximum  |
| <b>Head Style:</b>                                    | Dished Hexagon   |
| <b>Head Height:</b>                                   | 0.188 Inches Minimum And 0.203 Inches Maximum  |
| <b>Width Between Flats:</b>                           | 0.553 Inches Minimum And 0.564 Inches Maximum  |
| <b>Grip Diameter:</b>                                 | 0.3735 Inches Minimum And 0.3745 Inches Maximum  |
| <b>Nominal Thread Diameter:</b>                       | 0.375 Inches   |
| <b>Grip Length:</b>                                   | 1.865 Inches Minimum And 1.885 Inches Maximum  |
| <b>Thread Quantity Per Inch:</b>                      | 24   |
| <b>Minimum Tensile Strength:</b>                      | 95000 Pounds Per Square Inch   |
| <b>Surface Finish:</b>                                | 32.0 Microinches Bearing Surface Of Head   |
| <b>Surface Finish:</b>                                | 32.0 Microinches Grip  |
| <b>Surface Finish:</b>                                | 32.0 Microinches Threads   |
| <b>Part Name Assigned By Controlling Agency:</b>      | Bolt, Hex Head, 95 Ksi Shear, Short Thread, A286, Nonlocking   |
| <b>Special Features:</b>                              | Drilled Shank With Nominal Hole Diameter Of 0.106 Inches Centered 0.216 Inches From Threaded End                           |
| <b>Material:</b>                                      | Steel Corrosion Resisting Overall  |
| <b>Material Document And Classification:</b>          | Ams 5737 Assn Std Single Material Response Overall Or Ams 5853 Assn Std Single Material Response Overall                   |
| <b>Surface Treatment:</b>                             | Passivate Overall  |
| <b>Surface Treatment Document And Classification:</b> | Ams 2700, Type 2 Assn Std Single Treatment Response Overall Or Ams 2700, Type 8 Assn Std Single Treatment Response Overall |
| <b>Thread Series Designator:</b>                      | Unjf   |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30LJ6DU30> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.