

P/N BACB30LK2-5

Description

Fastener Length: 43/64", Thread: 8-32, Thread Length: 11/32"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: BACB30LK25

Minimum Qty (MOQ): 5 EA

NSN: 5305-01-231-2206

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N BACB30LK2-5 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.345 Inches Nominal
Fastener Length:	0.6425 Inches Minimum And 0.6725 Inches Maximum
Head Style:	Pan
Head Diameter:	0.306 Inches Minimum And 0.322 Inches Maximum
Head Height:	0.105 Inches Minimum And 0.115 Inches Maximum
Grip Diameter:	0.1630 Inches Minimum And 0.1635 Inches Maximum
Single Shear Strength:	95000 Pounds Per Square Inch
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Grip Length:	0.3025 Inches Minimum And 0.3225 Inches Maximum
Thread Quantity Per Inch:	32
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,type Ii,class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjc

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/close+tolerance+screws/BACB30LK2-5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/close+tolerance+screws/BACB30LK2-5 and selecting the quantity you