

## P/N BACB30LK2U4

### **Description**

Fastener Length: 39/64", Thread: 8-32, Thread Length: 11/32"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model:	BACB30LK2U4
Minimum Qty (MOQ):	10 EA
NSN:	5305-01-581-4775
Schedule B:	7318.15.8085
ECCN:	9A991



<sup>\*</sup> See page 2 for technical characteristics

# P/N BACB30LK2U4 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.340 Inches Minimum And 0.350 Inches Maximum
Fastener Length:	0.580 Inches Minimum And 0.610 Inches Maximum
Head Style:	Pan
Head Diameter:	0.306 Inches Minimum And 0.322 Inches Maximum
Head Height:	0.105 Inches Minimum And 0.115 Inches Maximum
Grip Diameter:	0.1630 Inches Minimum And 0.1635 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Grip Length:	0.240 Inches Minimum And 0.260 Inches Maximum
Thread Quantity Per Inch:	32
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Amsqq-p-35, Ty li Or Ty Viii Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjc

## **How to Order**

Order this bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/machine+bolts/BACB30LK2U4">https://military-fasteners.com/bolts/machine+bolts/BACB30LK2U4</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.