

**Description**

Fastener Length: 51/64", Thread: 8-32, Thread Length: 23/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                                           |
|-------------------------|-------------------------------------------|
| SKU / Model:            | BACB30LK2U7                               |
| Minimum Qty (MOQ):      | 40 EA                                     |
| NSN:                    | 5305-01-207-9350                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | 9A991                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N BACB30LK2U7 Specifications

|                                                       |                                                    |
|-------------------------------------------------------|----------------------------------------------------|
| <b>Thread Class:</b>                                  | 3a                                                 |
| <b>Thread Direction:</b>                              | Right-hand                                         |
| <b>Thread Length:</b>                                 | 0.320 Inches Minimum And 0.370 Inches Maximum      |
| <b>Fastener Length:</b>                               | 0.768 Inches Minimum And 0.798 Inches Maximum      |
| <b>Head Style:</b>                                    | Pan                                                |
| <b>Head Diameter:</b>                                 | 0.306 Inches Minimum And 0.322 Inches Maximum      |
| <b>Head Height:</b>                                   | 0.105 Inches Minimum And 0.115 Inches Maximum      |
| <b>Grip Diameter:</b>                                 | 0.1630 Inches Minimum And 0.1635 Inches Maximum    |
| <b>Internal Drive Style:</b>                          | Cross Recess Type 1                                |
| <b>Nominal Thread Diameter:</b>                       | 0.164 Inches                                       |
| <b>Grip Length:</b>                                   | 0.428 Inches Minimum And 0.448 Inches Maximum      |
| <b>Thread Quantity Per Inch:</b>                      | 32                                                 |
| <b>Surface Finish:</b>                                | 32.0 Microinches Bearing Surface Of Head           |
| <b>Surface Finish:</b>                                | 32.0 Microinches Grip                              |
| <b>Surface Finish:</b>                                | 32.0 Microinches Threads                           |
| <b>Material:</b>                                      | Iron Alloy 660 Overall                             |
| <b>Material Document And Classification:</b>          | Ams 5737 Assn Std Single Material Response Overall |
| <b>Surface Treatment:</b>                             | Passivate Overall                                  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec Single Treatment Response Overall |
| <b>Thread Series Designator:</b>                      | Unjc                                               |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30LK2U7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.