

P/N BACB30LK3-4

Military-Fasteners.com

Description

Fastener Length: 39/64", Thread: 10-32, Thread Length: 23/64"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	BACB30LK34
Minimum Qty (MOQ):	15 EA
NSN:	5305-01-054-4636
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	013680, Alum Screws



P/N BACB30LK3-4 Specifications

Thread Class:	За
Thread Direction:	Right-hand
Thread Length:	0.320 Inches Minimum And 0.370 Inches Maximum
Fastener Length:	0.580 Inches Minimum And 0.610 Inches Maximum
Head Style:	Pan
Head Diameter:	0.357 Inches Minimum And 0.373 Inches Maximum
Head Height:	0.122 Inches Minimum And 0.133 Inches Maximum
Grip Diameter:	0.1885 Inches Minimum And 0.1895 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
End Item Identification:	Joint Stars Target Radar Sys;aircraft, Stratofortress B-52;e-3a Awacs
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.240 Inches Minimum And 0.260 Inches Maximum
Thread Quantity Per Inch:	32
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Iron Alloy 660 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <u>https://military-fasteners.com/screws/close+tolerance+screws/BACB30LK3-4</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.