

## P/N BACB30LK3-7

### **Description**

Fastener Length: 51/64", Thread: 10-32, Thread Length: 23/64"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: BACB30LK37

Minimum Qty (MOQ): 5 EA

NSN: 5305-01-202-8979

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# **P/N BACB30LK3-7 Specifications**

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.320 Inches Minimum And 0.370 Inches Maximum
Fastener Length:	0.768 Inches Minimum And 0.798 Inches Maximum
Head Style:	Pan
Head Diameter:	0.357 Inches Minimum And 0.373 Inches Maximum
Head Height:	0.122 Inches Minimum And 0.133 Inches Maximum
Grip Diameter:	0.1885 Inches Minimum And 0.1895 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.428 Inches Minimum And 0.448 Inches Maximum
Thread Quantity Per Inch:	32
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5731 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

## **How to Order**

Order this screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/close+tolerance+screws/BACB30LK3-7">https://military-fasteners.com/screws/close+tolerance+screws/BACB30LK3-7</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.