

Description

pan head

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|-------------------------------|
| SKU / Model: | BACB30LK3K2 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5305-01-597-1257 |
| ECCN: | EAR99 |
| National Motor Freight: | 096640, Screws, Iron Or Steel |



* See page 2 for technical characteristics

P/N BACB30LK3K2 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.345 Inches Nominal |
| Fastener Length: | 0.455 Inches Minimum And 0.485 Inches Maximum |
| Head Style: | Pan |
| Head Diameter: | 0.357 Inches Minimum And 0.373 Inches Maximum |
| Head Height: | 0.122 Inches Minimum And 0.133 Inches Maximum |
| Grip Diameter: | 0.1881 Inches Minimum And 0.1895 Inches Maximum |
| Internal Drive Style: | Cross Recess Type Iii |
| End Item Identification: | E-3 Aircraft |
| Nominal Thread Diameter: | 0.190 Inches |
| Grip Length: | 0.125 Inches Nominal |
| Thread Quantity Per Inch: | 32 |
| Part Name Assigned By Controlling Agency: | Bolt, Pan Head, Cross Recess, Short Thread, Close Tol, A286 Cres |
| Material: | Steel Corrosion Resisting Overall |
| Material Document And Classification: | Ams 5737 Assn Std Single Material Response Overall |
| Surface Treatment: | Aluminum Overall |
| Surface Treatment Document And Classification: | Bms10-85, Ty 1, Cl A Assn Std Single Treatment Response Overall |
| Thread Series Designator: | Unjc |

How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/BACB30LK3K2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.