

P/N BACB30LK3K3

Description

Fastener Length: 17/32", Hole Diameter: 1/16", Thread: 10-32, Thread Length: 11/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACB30LK3K3
Minimum Qty (MOQ):	10 EA
NSN:	5305-01-517-3070
Schedule B:	7318.15.8085
ECCN:	EAR99



^{*} See page 2 for technical characteristics

P/N BACB30LK3K3 Specifications

Thread Class:	3a
- 33 33 33 33 33 33 33 33 33 33 33 33 33	
Thread Direction:	Right-hand
Thread Length:	0.345 Inches Nominal
Fastener Length:	0.532 Inches Nominal
Head Style:	Pan
Head Diameter:	0.357 Inches Minimum And 0.373 Inches Maximum
Head Height:	0.122 Inches Minimum And 0.133 Inches Maximum
Hole Diameter:	0.070 Inches Minimum And 0.075 Inches Maximum
Grip Diameter:	0.1879 Inches Minimum And 0.1885 Inches Maximum
Internal Drive Style:	Cross Recess Type Ii
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.187 Inches Nominal
Hole Quantity:	2
Hole Type:	Drilled
Thread Quantity Per Inch:	32
Hole Configuration Style:	Round
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unjc

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/BACB30LK3K3 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.