

## P/N BACB30LK3U5

### **Description**

Fastener Length: 43/64", Thread: 10-32, Thread Length: 23/64"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: BACB30LK3U5

Minimum Qty (MOQ): 10 EA

NSN: 5305-01-207-9351

Schedule B: 7318.15.8085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N BACB30LK3U5 Specifications

| Thread Class:                                  | 3a   |
|--|--|
| Thread Direction:                              | Right-hand   |
| Thread Length:                                 | 0.320 Inches Minimum And 0.370 Inches Maximum      |
| Fastener Length:                               | 0.642 Inches Minimum And 0.672 Inches Maximum      |
| Head Style:                                    | Pan  |
| Head Diameter:                                 | 0.357 Inches Minimum And 0.373 Inches Maximum      |
| Head Height:                                   | 0.122 Inches Minimum And 0.133 Inches Maximum      |
| Grip Diameter:                                 | 0.1890 Inches Minimum And 0.1895 Inches Maximum    |
| Internal Drive Style:                          | Cross Recess Type 1                                |
| Nominal Thread Diameter:                       | 0.190 Inches                                       |
| Grip Length:                                   | 0.302 Inches Minimum And 0.322 Inches Maximum      |
| Thread Quantity Per Inch:                      | 32   |
| Surface Finish:                                | 32.0 Microinches Bearing Surface Of Head           |
| Surface Finish:                                | 32.0 Microinches Grip                              |
| Surface Finish:                                | 32.0 Microinches Threads                           |
| Material:                                      | Iron Alloy 660 Overall                             |
| Material Document And Classification:          | Ams 5737 Assn Std Single Material Response Overall |
| Surface Treatment:                             | Passivate Overall                                  |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Thread Series Designator:                      | Unjf   |

## **How to Order**

Order this bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/machine+bolts/BACB30LK3U5">https://military-fasteners.com/bolts/machine+bolts/BACB30LK3U5</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.