



Military-Fasteners.com

P/N BACB30LK3U7

Description

Fastener Length: 51/64", Thread: 10-32, Thread Length: 23/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

|                         |   |
|-------------------------|---|
| SKU / Model:            | BACB30LK3U7                               |
| Minimum Qty (MOQ):      | 15 EA                                     |
| NSN:                    | 5305-00-001-9753                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



\* See page 2 for technical characteristics

## P/N BACB30LK3U7 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3a   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Thread Length:</b>                                 | 0.320 Inches Minimum And 0.370 Inches Maximum      |
| <b>Fastener Length:</b>                               | 0.768 Inches Minimum And 0.798 Inches Maximum      |
| <b>Head Style:</b>                                    | Pan  |
| <b>Head Diameter:</b>                                 | 0.357 Inches Minimum And 0.373 Inches Maximum      |
| <b>Head Height:</b>                                   | 0.122 Inches Minimum And 0.133 Inches Maximum      |
| <b>Grip Diameter:</b>                                 | 0.1890 Inches Minimum And 0.1895 Inches Maximum    |
| <b>Internal Drive Style:</b>                          | Cross Recess Type 1                                |
| <b>Nominal Thread Diameter:</b>                       | 0.190 Inches                                       |
| <b>Grip Length:</b>                                   | 0.428 Inches Minimum And 0.448 Inches Maximum      |
| <b>Thread Quantity Per Inch:</b>                      | 32   |
| <b>Surface Finish:</b>                                | 32.0 Microinches Bearing Surface Of Head           |
| <b>Surface Finish:</b>                                | 32.0 Microinches Grip                              |
| <b>Surface Finish:</b>                                | 32.0 Microinches Threads                           |
| <b>Material:</b>                                      | Iron Alloy 660 Overall                             |
| <b>Material Document And Classification:</b>          | Ams 5737 Assn Std Single Material Response Overall |
| <b>Surface Treatment:</b>                             | Passivate Overall                                  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec Single Treatment Response Overall |
| <b>Thread Series Designator:</b>                      | Unjf   |
| <b>Specification/standard Data:</b>                   | 81205-bacb30lk Manufacturers Standard              |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30LK3U7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.