

P/N BACB30LK4-12

Description

Fastener Length: 1-9/64", Thread: 1/4-28, Thread Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: BACB30LK412

Minimum Qty (MOQ): 10 EA

NSN: 5305-01-365-0401

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N BACB30LK4-12 Specifications

| Thread Class: | 3a |
|--|---|
| Thread Direction: | Right-hand |
| Thread Length: | 0.389 Inches Nominal |
| Fastener Length: | 1.124 Inches Minimum And 1.154 Inches Maximum |
| Head Style: | Pan |
| Head Diameter: | 0.473 Inches Minimum And 0.492 Inches Maximum |
| Head Height: | 0.162 Inches Minimum And 0.175 Inches Maximum |
| Grip Diameter: | 0.2485 Inches Minimum And 0.2495 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.250 Inches |
| Grip Length: | 0.740 Inches Minimum And 0.760 Inches Maximum |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 95000 Pounds Per Square Inch |
| Surface Finish: | 32.0 Microinches Bearing Surface Of Head32.0 Microinches Grip32.0 Microinches Threads |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams 5737 Assn Std Single Material Response Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416 Ty 2 Cl 2 Fed Spec All Treatment Responses Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/close+tolerance+screws/BACB30LK4-12 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.