

**Description**

Fastener Length: 3-5/32", Thread: 5/8-18, Thread Length: 59/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | BACB30LM10DU36                            |
| Minimum Qty (MOQ):      | 1 EA                                      |
| NSN:                    | 5306-01-206-7228                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



\* See page 2 for technical characteristics

## P/N BACB30LM10DU36 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>  | 3a  |
| <b>Thread Direction:</b>  | Right-hand  |
| <b>Thread Length:</b>   | 0.877 Inches Minimum And 0.927 Inches Maximum                       |
| <b>Fastener Length:</b>   | 3.137 Inches Minimum And 3.167 Inches Maximum                       |
| <b>Head Style:</b>  | Dished Hexagon  |
| <b>Head Height:</b>   | 0.312 Inches Minimum And 0.327 Inches Maximum                       |
| <b>Width Between Flats:</b>   | 0.928 Inches Minimum And 0.940 Inches Maximum                       |
| <b>Grip Diameter:</b>   | 0.6235 Inches Minimum And 0.6240 Inches Maximum                     |
| <b>Shank Unthreaded Hole Diameter:</b>                                  | 0.141 Inches Minimum First Hole And 0.151 Inches Maximum First Hole |
| <b>Nominal Thread Diameter:</b>   | 0.625 Inches  |
| <b>Grip Length:</b>   | 2.240 Inches Minimum And 2.260 Inches Maximum                       |
| <b>Thread Quantity Per Inch:</b>  | 18  |
| <b>Minimum Tensile Strength:</b>  | 160000 Pounds Per Square Inch                                       |
| <b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b> | 2.878 Inches Minimum First Hole And 2.928 Inches Maximum First Hole |
| <b>Surface Finish:</b>  | 32.0 Microinches Bearing Surface Of Head                            |
| <b>Surface Finish:</b>  | 32.0 Microinches Grip   |
| <b>Surface Finish:</b>  | 32.0 Microinches Threads  |
| <b>Material:</b>  | Iron Alloy 660 Overall  |
| <b>Material Document And Classification:</b>                            | Ams 5737 Assn Std Single Material Response Overall                  |
| <b>Surface Treatment:</b>   | Passivate Overall   |
| <b>Surface Treatment Document And Classification:</b>                   | Qq-p-35 Fed Spec Single Treatment Response Overall                  |
| <b>Thread Series Designator:</b>  | Unf   |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30LM10DU36> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.