

Description

Fastener Length: 1-11/64", Thread: 10-32, Thread Length: 23/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACB30LM313
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-040-4702
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N BACB30LM3-13 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.320 Inches Minimum And 0.370 Inches Maximum
Fastener Length:	1.142 Inches Minimum And 1.172 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.110 Inches Minimum And 0.125 Inches Maximum
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Grip Diameter:	0.1885 Inches Minimum And 0.1895 Inches Maximum
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.802 Inches Minimum And 0.822 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Iron Alloy 660 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	81205-bacb30lm Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30LM3-13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.