

**Description**

Fastener Length: 1-53/64", Thread: 10-32, Thread Length: 11/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                    |                  |
|--------------------|------------------|
| SKU / Model:       | BACB30LM320      |
| Minimum Qty (MOQ): | 5 EA             |
| NSN:               | 5306-01-581-5681 |
| Schedule B:        | 7318.15.8085     |
| ECCN:              | EAR99            |



\* See page 2 for technical characteristics

## P/N BACB30LM3-20 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3a  |
| <b>Thread Direction:</b>                              | Right-hand  |
| <b>Thread Length:</b>                                 | 0.340 Inches Minimum And 0.350 Inches Maximum                               |
| <b>Fastener Length:</b>                               | 1.785 Inches Minimum And 1.840 Inches Maximum                               |
| <b>Head Style:</b>                                    | Dished Hexagon  |
| <b>Head Height:</b>                                   | 0.110 Inches Minimum And 0.125 Inches Maximum                               |
| <b>Width Between Flats:</b>                           | 0.367 Inches Minimum And 0.376 Inches Maximum                               |
| <b>Grip Diameter:</b>                                 | 0.1885 Inches Minimum And 0.1895 Inches Maximum                             |
| <b>Nominal Thread Diameter:</b>                       | 0.190 Inches  |
| <b>Grip Length:</b>                                   | 1.240 Inches Minimum And 1.260 Inches Maximum                               |
| <b>Thread Quantity Per Inch:</b>                      | 32  |
| <b>Minimum Tensile Strength:</b>                      | 160000 Pounds Per Square Inch   |
| <b>Surface Finish:</b>                                | 32.0 Microinches Bearing Surface Of Head                                    |
| <b>Surface Finish:</b>                                | 32.0 Microinches Grip   |
| <b>Surface Finish:</b>                                | 32.0 Microinches Threads  |
| <b>Part Name Assigned By Controlling Agency:</b>      | Bolt, Hex Head, 160 Ksi Min Tensile, Long Thread, A286, Nonlocking, Nominal |
| <b>Material:</b>                                      | Steel Corrosion Resisting Overall   |
| <b>Material Document And Classification:</b>          | Ams 5737 Assn Std Single Material Response Overall                          |
| <b>Surface Treatment:</b>                             | Cadmium Overall   |
| <b>Surface Treatment Document And Classification:</b> | Amsqq-p-416, Ty 2, Cl 2 Assn Std Single Treatment Response Overall          |
| <b>Thread Series Designator:</b>                      | Unjf  |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30LM3-20> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.