

Description

Fastener Length: 1-53/64", Thread: 10-32, Thread Length: 11/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACB30LM320
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-581-5681
Schedule B:	7318.15.8085
ECCN:	EAR99



* See page 2 for technical characteristics

P/N BACB30LM3-20 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.340 Inches Minimum And 0.350 Inches Maximum
Fastener Length:	1.785 Inches Minimum And 1.840 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.110 Inches Minimum And 0.125 Inches Maximum
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Grip Diameter:	0.1885 Inches Minimum And 0.1895 Inches Maximum
Nominal Thread Diameter:	0.190 Inches
Grip Length:	1.240 Inches Minimum And 1.260 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Part Name Assigned By Controlling Agency:	Bolt, Hex Head, 160 Ksi Min Tensile, Long Thread, A286, Nonlocking, Nominal
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Amsqq-p-416, Ty 2, Cl 2 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30LM3-20> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.