

## P/N BACB30LM3K2

### **Description**

Fastener Length: 11/32", Thread: 23/64-A32, Thread Length: 3/16"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: BACB30LM3K2

Minimum Qty (MOQ): 1 EA

NSN: 5306-01-604-8277

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# **P/N BACB30LM3K2 Specifications**

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.1900 Inches Nominal
Fastener Length:	0.345 Inches Nominal
Head Style:	Hexagon
Head Height:	0.110 Inches Minimum And 0.115 Inches Maximum
Width Between Flats:	0.410 Inches Nominal
Grip Diameter:	0.1879 Inches Minimum And 0.1885 Inches Maximum
End Item Identification:	E-3 Block 404
Nominal Thread Diameter:	0.367 Inches
Grip Length:	0.345 Inches Nominal
Thread Quantity Per Inch:	A32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Part Name Assigned By Controlling Agency:	Bolt,hex Head
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Ams Qq-p-426 Type Ii,class2 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf

## **How to Order**

Order this bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/machine+bolts/BACB30LM3K2">https://military-fasteners.com/bolts/machine+bolts/BACB30LM3K2</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.