

Description

Fastener Length: 11/32", Thread: 23/64-32, Thread Length: 3/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACB30LM3K3
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-604-8278
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N BACB30LM3K3 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.1900 Inches Nominal
Fastener Length:	0.345 Inches Nominal
Head Style:	Hexagon
Head Height:	0.110 Inches Minimum And 0.115 Inches Maximum
Width Between Flats:	0.19 Inches Nominal
Grip Diameter:	0.181 Inches Minimum And 0.184 Inches Maximum
End Item Identification:	E-3 Block 404
Nominal Thread Diameter:	0.367 Inches
Grip Length:	0.345 Inches Nominal
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Ams Qq-c-3230,class 2 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unj

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30LM3K3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.