

Description

Fastener Length: 1-23/64", Thread: 10-32, Thread Length: 23/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | BACB30LM3U16 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5306-01-211-3794 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N BACB30LM3U16 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.320 Inches Minimum And 0.370 Inches Maximum |
| Fastener Length: | 1.330 Inches Minimum And 1.360 Inches Maximum |
| Head Style: | Dished Hexagon |
| Head Height: | 0.110 Inches Minimum And 0.125 Inches Maximum |
| Width Between Flats: | 0.367 Inches Minimum And 0.376 Inches Maximum |
| Grip Diameter: | 0.1890 Inches Minimum And 0.1895 Inches Maximum |
| Nominal Thread Diameter: | 0.190 Inches |
| Grip Length: | 0.990 Inches Minimum And 1.010 Inches Maximum |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Surface Finish: | 32.0 Microinches Bearing Surface Of Head |
| Surface Finish: | 32.0 Microinches Grip |
| Surface Finish: | 32.0 Microinches Threads |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams 5737 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30LM3U16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.