

# P/N BACB30LM3U22

Military-Fasteners.com

#### Description

Fastener Length: 1-47/64", Thread: 10-32, Thread Length: 23/64"

\* Manufacturer certifications are shipped with your order  $\underline{\mathsf{FREE}}$  of charge

### Order this part online

#### **Additional Information**

SKU / Model:	BACB30LM3U22
Minimum Qty (MOQ):	10 EA
NSN:	5306-01-175-5700
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	096630, Screws Noi Brass / Bronze / Copper



### P/N BACB30LM3U22 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.330 Inches Minimum And 0.360 Inches Maximum
Fastener Length:	1.695 Inches Minimum And 1.745 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.110 Inches Minimum And 0.125 Inches Maximum
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Grip Diameter:	0.1890 Inches Minimum And 0.1895 Inches Maximum
Nominal Thread Diameter:	0.190 Inches
Grip Length:	1.365 Inches Minimum And 1.385 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

## How to Order

Order this bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/machine+bolts/BACB30LM3U22</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.