



Military-Fasteners.com

P/N BACB30LM4-9

Description

Fastener Length: 1-9/64", Thread: 1/4-28, Thread Length: 27/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACB30LM49
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-581-5663
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

# P/N BACB30LM4-9 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.420 Inches Minimum And 0.430 Inches Maximum
Fastener Length:	1.097 Inches Minimum And 1.152 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.125 Inches Minimum And 0.140 Inches Maximum
Width Between Flats:	0.430 Inches Minimum And 0.439 Inches Maximum
Grip Diameter:	0.2490 Inches Minimum And 0.2495 Inches Maximum
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.552 Inches Minimum And 0.572 Inches Maximum
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Part Name Assigned By Controlling Agency:	Bolt, Hex Head, 160 Ksi Min Tensile, Long Thread, A286, Nonlocking, Nominal
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Amsqq-p-416, Ty 2, Cl 2 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30LM4-9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.