

## Description

Fastener Length: 5-1/4", Thread: 1/4-28, Thread Length: 27/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

|                    |                  |
|--------------------|------------------|
| SKU / Model:       | BACB30LM4D75     |
| Minimum Qty (MOQ): | 1 EA             |
| NSN:               | 5306-01-581-5708 |
| Schedule B:        | 7318.15.2091     |
| ECCN:              | EAR99            |



# P/N BACB30LM4D75 Specifications

|  |  |
|--|--|
| Thread Class:                                  | 3a   |
| Thread Direction:                              | Right-hand   |
| Thread Length:                                 | 0.420 Inches Minimum And 0.430 Inches Maximum                                  |
| Fastener Length:                               | 5.212 Inches Minimum And 5.257 Inches Maximum                                  |
| Head Style:                                    | Dished Hexagon   |
| Head Height:                                   | 0.125 Inches Minimum And 0.140 Inches Maximum                                  |
| Width Between Flats:                           | 0.430 Inches Minimum And 0.439 Inches Maximum                                  |
| Grip Diameter:                                 | 0.2490 Inches Minimum And 0.2495 Inches Maximum                                |
| Nominal Thread Diameter:                       | 0.250 Inches   |
| Grip Length:                                   | 4.677 Inches Minimum And 4.697 Inches Maximum                                  |
| Thread Quantity Per Inch:                      | 28   |
| Minimum Tensile Strength:                      | 160000 Pounds Per Square Inch  |
| Surface Finish:                                | 32.0 Microinches Bearing Surface Of Head                                       |
| Surface Finish:                                | 32.0 Microinches Grip  |
| Surface Finish:                                | 32.0 Microinches Threads   |
| Part Name Assigned By Controlling Agency:      | Bolt, Hex Head, 160 Ksi Min Tensile, Long Thread, A286, Nonlocking, Nominal    |
| Special Features:                              | Drilled Shank Centered At Positon Approximately 0.178 Inches From Threaded End |
| Material:                                      | Steel Corrosion Resisting Overall  |
| Material Document And Classification:          | Ams 5737 Assn Std Single Material Response Overall                             |
| Surface Treatment:                             | Cadmium Overall  |
| Surface Treatment Document And Classification: | Amsqq-p-416, Ty 2, Cl 2 Assn Std Single Treatment Response Overall             |
| Thread Series Designator:                      | Unjf   |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30LM4D75> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.