

Description

Fastener Length: 25/32", Thread: 1/4-24, Thread Length: 15/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACB30LM58
Minimum Qty (MOQ):	1 EA
NSN:	5306-00-486-5530
Schedule B:	7318.15.8085
ECCN:	9A991

NO IMAGE
AVAILABLE

P/N BACB30LM5-8 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.469 Inches Maximum
Fastener Length:	0.782 Inches Nominal
Head Style:	Dished Hexagon
Head Height:	0.156 Inches Minimum And 0.171 Inches Maximum
Width Between Flats:	0.492 Inches Minimum And 0.502 Inches Maximum
Grip Diameter:	0.3110 Inches Minimum And 0.3120 Inches Maximum
Single Shear Strength:	95000 Pounds Per Square Inch
Nominal Thread Diameter:	0.312 Inches
Grip Length:	0.312 Inches Nominal
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30LM5-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.