

Description

Fastener Length: 25/32", Thread: 1/4-24, Thread Length: 31/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACB30LM5U5
Minimum Qty (MOQ):	1
NSN:	5306-01-053-6956
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N BACB30LM5U5 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.444 Inches Minimum And 0.494 Inches Maximum
Fastener Length:	0.766 Inches Minimum And 0.796 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.156 Inches Minimum And 0.171 Inches Maximum
Width Between Flats:	0.492 Inches Minimum And 0.502 Inches Maximum
Grip Diameter:	0.3115 Inches Minimum And 0.3120 Inches Maximum
Nominal Thread Diameter:	0.312 Inches
Grip Length:	0.302 Inches Minimum And 0.322 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Iron Alloy 660 Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unjf

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30LM5U5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.