

## P/N BACB30LM6D21

### **Description**

Fastener Length: 1-7/8", Hole Diameter: 7/64", Thread: 3/8-24, Thread Length: 9/16"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model:	BACB30LM6D21
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-517-4112
Schedule B:	7318.15.8085
ECCN:	EAR99



<sup>\*</sup> See page 2 for technical characteristics

# P/N BACB30LM6D21 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.578 Inches Nominal
Fastener Length:	1.890 Inches Nominal
Head Style:	Dished Hexagon
Head Height:	0.188 Inches Minimum And 0.203 Inches Maximum
Width Between Flats:	0.553 Inches Minimum And 0.564 Inches Maximum
Hole Diameter:	0.106 Inches Minimum And 0.116 Inches Maximum
Grip Diameter:	0.3729 Inches Minimum And 0.3735 Inches Maximum
Nominal Thread Diameter:	0.375 Inches
Grip Length:	1.312 Inches Nominal
Hole Quantity:	2
Hole Type:	Drilled
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hole Configuration Style:	Round
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unf

## **How to Order**

Order this bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/machine+bolts/BACB30LM6D21">https://military-fasteners.com/bolts/machine+bolts/BACB30LM6D21</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.