

P/N BACB30LM6D21

Description

Fastener Length: 1-7/8", Hole Diameter: 7/64", Thread: 3/8-24, Thread Length: 9/16"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

| SKU / Model: | BACB30LM6D21 |
|--------------------|------------------|
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5306-01-517-4112 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |



^{*} See page 2 for technical characteristics

P/N BACB30LM6D21 Specifications

| Thread Class: | 3a |
|---------------------------------------|----------------------------------------------------|
| Thread Direction: | Right-hand |
| Thread Length: | 0.578 Inches Nominal |
| Fastener Length: | 1.890 Inches Nominal |
| Head Style: | Dished Hexagon |
| Head Height: | 0.188 Inches Minimum And 0.203 Inches Maximum |
| Width Between Flats: | 0.553 Inches Minimum And 0.564 Inches Maximum |
| Hole Diameter: | 0.106 Inches Minimum And 0.116 Inches Maximum |
| Grip Diameter: | 0.3729 Inches Minimum And 0.3735 Inches Maximum |
| Nominal Thread Diameter: | 0.375 Inches |
| Grip Length: | 1.312 Inches Nominal |
| Hole Quantity: | 2 |
| Hole Type: | Drilled |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Hole Configuration Style: | Round |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams 5737 Assn Std Single Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Thread Series Designator: | Unf |

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/BACB30LM6D21 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.