



Military-Fasteners.com

P/N BACB30LR3-21

## Description

Fastener Length: 1-43/64", Thread: 10-32, Thread Length: 23/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

|                         |   |
|-------------------------|---|
| SKU / Model:            | BACB30LR321                               |
| Minimum Qty (MOQ):      | 5 EA                                      |
| NSN:                    | 5305-01-198-6509                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



\* See page 2 for technical characteristics

## P/N BACB30LR3-21 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3a   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Thread Length:</b>                                 | 0.320 Inches Minimum And 0.370 Inches Maximum                      |
| <b>Fastener Length:</b>                               | 1.642 Inches Minimum And 1.672 Inches Maximum                      |
| <b>Head Style:</b>                                    | Flat Countersunk   |
| <b>Head Diameter:</b>                                 | 0.337 Inches Minimum And 0.383 Inches Maximum                      |
| <b>Grip Diameter:</b>                                 | 0.1885 Inches Minimum And 0.1895 Inches Maximum                    |
| <b>Internal Drive Style:</b>                          | Cross Recess Type 1  |
| <b>End Item Identification:</b>                       | Aircraft, Stratolifter C-135                                       |
| <b>Nominal Thread Diameter:</b>                       | 0.190 Inches   |
| <b>Grip Length:</b>                                   | 1.302 Inches Minimum And 1.322 Inches Maximum                      |
| <b>Thread Quantity Per Inch:</b>                      | 32   |
| <b>Countersink Angle:</b>                             | 99.0 Degrees Minimum And 101.0 Degrees Maximum                     |
| <b>Surface Finish:</b>                                | 32.0 Microinches Grip  |
| <b>Surface Finish:</b>                                | 32.0 Microinches Threads   |
| <b>Material:</b>                                      | Iron Alloy 660 Overall   |
| <b>Material Document And Classification:</b>          | Ams 5737 Assn Std Single Material Response Overall                 |
| <b>Surface Treatment:</b>                             | Cadmium Overall And Chromate Overall                               |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416 Type 2 Class 2 Fed Spec Single Treatment Response Overall |
| <b>Thread Series Designator:</b>                      | Unjf   |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30LR3-21> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.