

Description

Fastener Length: 2-7/16", Thread: 1/4-28, Thread Length: 7/16",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACB30LR432
Minimum Qty (MOQ):	1
NSN:	5305-01-056-2951
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N BACB30LR4-32 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.400 Inches Minimum And 0.450 Inches Maximum
Fastener Length:	2.410 Inches Minimum And 2.440 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.455 Inches Minimum And 0.510 Inches Maximum
Grip Diameter:	0.2485 Inches Minimum And 0.2495 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.250 Inches
Grip Length:	1.990 Inches Minimum And 2.010 Inches Maximum
Thread Quantity Per Inch:	28
Countersink Angle:	100.0 Degrees Nominal
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Iron Alloy 660 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30LR4-32> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.