

Description

Fastener Length: 43/64", Thread: 1/4-28, Thread Length: 27/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACB30LR44
Minimum Qty (MOQ):	10 EA
NSN:	5306-01-520-8956



P/N BACB30LR4-4 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.425 Inches Nominal
Fastener Length:	0.675 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.455 Inches Minimum And 0.510 Inches Maximum
Locking Feature:	Pellet Locking Feature
Grip Diameter:	0.2481 Inches Minimum And 0.2485 Inches Maximum
Shank Unthreaded Hole Diameter:	0.076 Inches Nominal Overall
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.250 Inches Nominal
Thread Quantity Per Inch:	28
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Distance From Head Largest Bearing Surface To Shank Hole Center:	2.6845 Inches Nominal First Hole
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	Ams5737 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416, Type Ii, Class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30LR4-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.