

Description

Fastener Length: 63/64", Thread: 1/4-28, Thread Length: 27/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | BACB30LR49 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5306-01-520-8957 |



P/N BACB30LR4-9 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.425 Inches Nominal |
| Fastener Length: | 0.9875 Inches Nominal |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.455 Inches Minimum And 0.510 Inches Maximum |
| Locking Feature: | Pellet Locking Feature |
| Grip Diameter: | 0.2481 Inches Minimum And 0.2485 Inches Maximum |
| Shank Unthreaded Hole Diameter: | 0.076 Inches Nominal Overall |
| Nominal Thread Diameter: | 0.250 Inches |
| Grip Length: | 0.5625 Inches Nominal |
| Thread Quantity Per Inch: | 28 |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Distance From Head Largest Bearing Surface To Shank Hole Center: | 2.6845 Inches Nominal First Hole |
| Material: | Steel Corrosion Resisting Overall |
| Material Document And Classification: | Ams5737 Assn Std Single Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416, Type Ii, Class 2 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30LR4-9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.