

Description

Fastener Length: 63/64", Thread: 1/4-28, Thread Length: 27/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACB30LR49
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-520-8957



\* See page 2 for technical characteristics

## P/N BACB30LR4-9 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.425 Inches Nominal
<b>Fastener Length:</b>	0.9875 Inches Nominal
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.455 Inches Minimum And 0.510 Inches Maximum
<b>Locking Feature:</b>	Pellet Locking Feature
<b>Grip Diameter:</b>	0.2481 Inches Minimum And 0.2485 Inches Maximum
<b>Shank Unthreaded Hole Diameter:</b>	0.076 Inches Nominal Overall
<b>Nominal Thread Diameter:</b>	0.250 Inches
<b>Grip Length:</b>	0.5625 Inches Nominal
<b>Thread Quantity Per Inch:</b>	28
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b>	2.6845 Inches Nominal First Hole
<b>Material:</b>	Steel Corrosion Resisting Overall
<b>Material Document And Classification:</b>	Ams5737 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416, Type II, Class 2 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30LR4-9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.