

Description

Fastener Length: 1-9/16", Thread: 1/4-28, Thread Length: 27/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACB30LR4U18
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-591-9951

NO IMAGE
AVAILABLE

P/N BACB30LR4U18 Specifications

Thread Direction:	Right-hand
Thread Length:	0.425 Inches Nominal
Fastener Length:	1.535 Inches Minimum And 1.565 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	1.115 Inches Minimum And 1.135 Inches Maximum
Grip Diameter:	0.249 Nominal Mils And 0.250 Nominal Centimeters
Internal Drive Style:	Cross Recess Type li
Nominal Thread Diameter:	0.250 Inches
Grip Length:	1.115 Nominal Mils And 1.135 Nominal Centimeters
Thread Quantity Per Inch:	28
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Part Name Assigned By Controlling Agency:	Bolt, 100 Head, Cross Recess, Long Thd, Clos Tolerance
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30LR4U18> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.